## NSN 4140-01-008-6522

Tubeaxial Fan - Page 1 of 2

**Enamel housing** 



View Online at https://aerobasegroup.com/nsn/4140-01-008-6522 **Speed Adjustments:** Single speed Length: 1.500 inches Flow Direction: Outward **Ambient Tempurature At Full Rated Power:** -20.0 degrees fahrenheit and 158.0 degrees fahrenheit **Operating Speed At Rated Capacity In Rpm:** 3200.0 **Electrical Connection Type:** Terminal block Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water **Drive Type:** Direct **Prime Mover Type:** Electric motor **Inclosure Type:** Fully enclosed **Mounting Facility Type And Quantity:** 2 flange and 4 threaded hole and 4 unthreaded hole **Rotation Direction For Which Designed:** Counterclockwise Air Flow Rate: 100.0 cubic feet per minute **Voltage In Volts And Current Type:** 115.0 ac **Housing Inside Diameter:** 4.517 inches **Prime Mover Drive Shaft Bearing Type:** Sleeve Phase: Single **Special Features:** 4.687 in. Square flange both ends of venturi tube w/holes ea corner, holes in motor end flange tapped 8-32 unc 2b Frequency In Hertz: 50.0 and 60.0 Material: Zinc housing **Surface Treatment:** 

## NSN 4140-01-008-6522

Tubeaxial Fan - Page 2 of 2



Style Designator:
Fixed
Shelf Life:
N/a
Unit Of Measure:

**Demilitarization:** No

Fiig:

A087a0