

View Online at <https://aerobasegroup.com/nsn/4140-01-015-2727>

Speed Adjustments:

Single speed

Length:

2.400 inches

Flow Direction:

Inward

Environmental Protection:

Fungus resistant and humidity proof and shock proof and vibration proof and salt spray resistant

Ambient Temperature At Full Rated Power:

-20.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

11000.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

190.0 cubic feet per minute

Voltage In Volts And Current Type:

148.0 ac

Housing Inside Diameter:

3.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

U/w sanders associates inc p/n 800186 inverter to produce 148 volts avg sq wave

Frequency In Hertz:

400.0

Material:

Aluminum

Surface Treatment:

Chromate and enamel

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response and tt-e-489 federal specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-c-5541 spec.