

View Online at <https://aerobasegroup.com/nsn/4140-01-015-2727>

**Speed Adjustments:**

Single speed

**Length:**

2.400 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Fungus resistant and humidity proof and shock proof and vibration proof and salt spray resistant

**Ambient Temperature At Full Rated Power:**

-20.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

11000.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 rim

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

190.0 cubic feet per minute

**Voltage In Volts And Current Type:**

148.0 ac

**Housing Inside Diameter:**

3.500 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Special Features:**

U/w sanders associates inc p/n 800186 inverter to produce 148 volts avg sq wave

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Surface Treatment:**

Chromate and enamel

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response and tt-e-489 federal specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-c-5541 spec.