

View Online at <https://aerobasegroup.com/nsn/4140-01-019-8539>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

5.125 inches

**Length:**

7.281 inches

**Environmental Protection:**

Fungus resistant and humidity proof and moisture resistant and shock proof and vibration proof and salt spray resistant

**Ambient Temperature At Full Rated Power:**

85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3200.0

**Electrical Connection Type:**

Connector receptacle

**Outlet Inside Width:**

2.875 inches

**Outlet Inside Height:**

1.594 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

175.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.161 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Single

**Special Features:**

Connector receptacle rotated 90 deg

**Height:**

7.844 inches

**Material:**

Steel

**Surface Treatment:**

Zinc blade

**Style Designator:**

Fixed, inverted, rectangular outlet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0