

View Online at <https://aerobasegroup.com/nsn/4140-01-020-9926>

**Stage Quantity:**

1

**Length:**

8.380 inches

**Flow Direction:**

Outward

**Operating Speed At Rated Capacity In Rpm:**

7600.0

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Belt

**Mounting Facility Type And Quantity:**

8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

3450.0 cubic feet per minute

**Housing Inside Diameter:**

9.200 inches

**Shaft Bearing Type:**

Ball

**Special Features:**

Impeller shaft extended 2.00 in. Inlet end with no. 405 woodruff key slot 1 in. From end of shaft

**Material:**

Aluminum housing

**Unpackaged Unit Weight:**

23.000 pounds

**Surface Treatment:**

Enamel semigloss housing outside

**Style Designator:**

Fixed

**Supplementary Features:**

Xw/motor mtg flat on venturi tube provided w/4 holes tapped 1/4-20 nc-2 by 0.375 in @dp, spaced as rectangular pattern 4.00 in. By 4.75 in., 4.00 in. Dim on longitudinal axis of venturi, 1st hole located 2.0 in. From shaft end of venturi

**Test Data Document:**

13499-009-0225 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0