

View Online at <https://aerobasegroup.com/nsn/4140-01-020-9926>

Stage Quantity:

1

Length:

8.380 inches

Flow Direction:

Outward

Operating Speed At Rated Capacity In Rpm:

7600.0

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Belt

Mounting Facility Type And Quantity:

8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

3450.0 cubic feet per minute

Housing Inside Diameter:

9.200 inches

Shaft Bearing Type:

Ball

Special Features:

Impeller shaft extended 2.00 in. Inlet end with no. 405 woodruff key slot 1 in. From end of shaft

Material:

Aluminum housing

Unpackaged Unit Weight:

23.000 pounds

Surface Treatment:

Enamel semigloss housing outside

Style Designator:

Fixed

Supplementary Features:

Xw/motor mtg flat on venturi tube provided w/4 holes tapped 1/4-20 nc-2 by 0.375 in @dp, spaced as rectangular pattern 4.00 in. By 4.75 in., 4.00 in. Dim on longitudinal axis of venturi, 1st hole located 2.0 in. From shaft end of venturi

Test Data Document:

13499-009-0225 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0