

View Online at <https://aerobasegroup.com/nsn/4140-01-021-2010>

**Speed Adjustments:**

Three speed

**Length:**

1.500 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Dustproof and fungus resistant and moisture resistant and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-25.0 degrees celsius and 185.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3400.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

94.0 cubic feet per minute and 120.0 cubic feet per minute and 130.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

14.000 watts and 13.000 watts and 41.000 watts

**Housing Inside Diameter:**

4.517 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

50.0 and 60.0 and 400.0

**Material:**

Zinc housing

**Surface Treatment:**

Enamel lusterless housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0