

View Online at <https://aerobasegroup.com/nsn/4140-01-021-2010>

Speed Adjustments:

Three speed

Length:

1.500 inches

Flow Direction:

Outward

Environmental Protection:

Dustproof and fungus resistant and moisture resistant and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-25.0 degrees celsius and 185.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3400.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

94.0 cubic feet per minute and 120.0 cubic feet per minute and 130.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

14.000 watts and 13.000 watts and 41.000 watts

Housing Inside Diameter:

4.517 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

50.0 and 60.0 and 400.0

Material:

Zinc housing

Surface Treatment:

Enamel lusterless housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0