

View Online at <https://aerobasegroup.com/nsn/4140-01-022-7608>

Speed Adjustments:

Single speed

Length:

1.500 inches

Flow Direction:

Inward

Environmental Protection:

Humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 100.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

2000.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

62.0 cubic feet per minute and 79.0 cubic feet per minute and 82.0 cubic feet per minute

Voltage In Volts And Current Type:

16.5 ac

Prime Mover Power Rating:

4.200 watts

Housing Inside Diameter:

4.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

Altitude rating 10000 ft operating, 50000 ft non-operating, additional operating speed at rated capacity in rpm 2300.0 and 2500, additional voltages 23.5 ac @and 30.5 ac

Frequency In Hertz:

90.0

Material:

Plastic polycarbonate blade

Surface Treatment:

Enamel housing

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.