

View Online at <https://aerobasegroup.com/nsn/4140-01-023-1537>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Diameter:**

1.870 inches

**Length:**

1.580 inches

**Flow Direction:**

Outward

**Ambient Temperature At Full Rated Power:**

125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

10400.0

**Electrical Connection Type:**

Connector plug

**Static Pressure At Specificationified Air Flow Rate:**

0.8 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 4 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

29.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.014 horsepower

**Housing Inside Diameter:**

1.890 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Special Features:**

W/sq flange mtg adapter; 6 in. Lg connector cord w/vinyl sleeving; 200v 0.18 microfarad capacitor furnished

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy

**Quantity:**

1

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Mil-e-5557, type 4 military specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-e-5557 spec.