

View Online at <https://aerobasegroup.com/nsn/4140-01-024-2257>

Speed Adjustments:

Single speed

Length:

1.500 inches

Flow Direction:

Inward

Environmental Protection:

Shock proof and vibration proof and salt spray resistant

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

5200.0

Electrical Connection Type:

Connector

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

180.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.049 horsepower

Housing Inside Diameter:

4.009 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

H4.68 in. Sq flange both ends of venturi tube, discharge end flange 0.330 in. Diameter hole ea corner, 0.166 in. Diameter holes ea corner intake end flange, special machining of flange corners and notching 1 corner

Frequency In Hertz:

400.0

Material:

Plastic polycarbonate blade

Surface Treatment:

Enamel lusterless housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0