

View Online at <https://aerobasegroup.com/nsn/4140-01-024-2257>

**Speed Adjustments:**

Single speed

**Length:**

1.500 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Shock proof and vibration proof and salt spray resistant

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

5200.0

**Electrical Connection Type:**

Connector

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

180.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.049 horsepower

**Housing Inside Diameter:**

4.009 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Special Features:**

H4.68 in. Sq flange both ends of venturi tube, discharge end flange 0.330 in. Diameter hole ea corner, 0.166 in. Diameter holes ea corner intake end flange, special machining of flange corners and notching 1 corner

**Frequency In Hertz:**

400.0

**Material:**

Plastic polycarbonate blade

**Surface Treatment:**

Enamel lusterless housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0