

View Online at <https://aerobasegroup.com/nsn/4140-01-024-5862>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

10.500 inches

Length:

8.891 inches

Environmental Protection:

Shock proof and vibration proof

Operating Speed At Rated Capacity In Rpm:

1700.0

Electrical Connection Type:

Wire lead

Outlet Inside Width:

4.188 inches

Outlet Inside Height:

3.672 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 4 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

225.0 cubic feet per minute

Outlet Location:

Bottom or top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Phase:

Single

Special Features:

Positioning when mtg determines discharge blast direction

Height:

9.781 inches

Material:

Steel

Surface Treatment:

Enamel housing

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0