

View Online at <https://aerobasegroup.com/nsn/4140-01-026-1378>

Speed Adjustments:

Single speed

Length:

0.984 inches

Flow Direction:

Inward

Environmental Protection:

Vibration proof

Ambient Temperature At Full Rated Power:

-10.0 degrees celsius and 70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

1500.0

Electrical Connection Type:

Connector plug

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Err Default:

Err default

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 6 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

17.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.008 horsepower

Housing Inside Diameter:

3.543 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

3.622 in. Sq mtg flange w/corner holes provided at both ends of venturi tube, rated 1450 rpm at 50 hz operation, class a insulation motor windings

Frequency In Hertz:

50.0 and 60.0

Material:

Zinc alloy housing

Surface Treatment:

Paint housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0