

View Online at <https://aerobasegroup.com/nsn/4140-01-026-1378>

**Speed Adjustments:**

Single speed

**Length:**

0.984 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Vibration proof

**Ambient Temperature At Full Rated Power:**

-10.0 degrees celsius and 70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

1500.0

**Electrical Connection Type:**

Connector plug

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Err Default:**

Err default

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 6 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

17.000 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.008 horsepower

**Housing Inside Diameter:**

3.543 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Special Features:**

3.622 in. Sq mtg flange w/corner holes provided at both ends of venturi tube, rated 1450 rpm at 50 hz operation, class a insulation motor windings

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Zinc alloy housing

**Surface Treatment:**

Paint housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0