

View Online at <https://aerobasegroup.com/nsn/4140-01-027-6019>

Speed Adjustments:

Single speed

Diameter:

6.500 inches

Length:

2.500 inches

Flow Direction:

Inward

Environmental Protection:

Humidity proof and shock proof and salt spray resistant and vibration proof

Ambient Temperature At Full Rated Power:

100.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3450.0

Electrical Connection Type:

Connector receptacle

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

290.000 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

0.037 horsepower

Housing Inside Diameter:

6.812 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Class f insulation motor windings

Frequency In Hertz:

400.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Enamel lusterless

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0