

View Online at <https://aerobasegroup.com/nsn/4140-01-027-6020>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

11.312 inches

Length:

9.281 inches

Environmental Protection:

Moisture resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

2790.0

Electrical Connection Type:

Connector receptacle

Outlet Inside Width:

4.500 inches

Outlet Inside Height:

2.906 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 4 threaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

600.0 cubic feet per minute

Outlet Location:

Bottom and top

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

1.032 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Blade Shape:

Forward curve

Phase:

Three

Special Features:

Alternate mtg provides optional discharge blast direction, inlet bellmouth cone end discharge flange provided w/unthreaded holes for mtg,
@class h insulation motor windings

Height:

10.375 inches

Material:

Steel

Quantity:

1

Surface Treatment:

Cadmium blade

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0