

View Online at <https://aerobasegroup.com/nsn/4140-01-027-6020>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

11.312 inches

**Length:**

9.281 inches

**Environmental Protection:**

Moisture resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2790.0

**Electrical Connection Type:**

Connector receptacle

**Outlet Inside Width:**

4.500 inches

**Outlet Inside Height:**

2.906 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 4 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

600.0 cubic feet per minute

**Outlet Location:**

Bottom and top

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

1.032 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Angular down and angular up and horizontal and vertical down and vertical up

**Blade Shape:**

Forward curve

**Phase:**

Three

**Special Features:**

Alternate mtg provides optional discharge blast direction, inlet bellmouth cone end discharge flange provided w/unthreaded holes for mtg,  
@class h insulation motor windings

**Height:**

10.375 inches

**Material:**

Steel

**Quantity:**

1

**Surface Treatment:**

Cadmium blade

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0