

View Online at <https://aerobasegroup.com/nsn/4140-01-028-0349>

Speed Adjustments:

Single speed

Length:

1.645 inches

Flow Direction:

Outward

Ambient Temperature At Full Rated Power:

-28.0 degrees celsius and 70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

2750.0 and 3250.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

37.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.014 horsepower

Housing Inside Diameter:

2.955 inches

Prime Mover Drive Shaft Bearing Type:

Sleeve

Phase:

Single

Special Features:

3.12 in. Sq flange w/hole in ea corner provided ea end of venturi tube, class a insulation motor windings

Frequency In Hertz:

50.0 and 60.0

Material:

Plastic polypropylene blade

Unpackaged Unit Weight:

1.125 pounds

Surface Treatment:

Enamel lusterless housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0