

View Online at <https://aerobasegroup.com/nsn/4140-01-028-1595>

Speed Adjustments:

Single speed

Length:

3.000 inches

Flow Direction:

Outward and inward

Environmental Protection:

Humidity proof and shock proof and vibration proof and salt spray resistant

Ambient Temperature At Full Rated Power:

65.0 degrees celsius

End Application:

Nato seasparrow sms project

Electrical Connection Type:

Connector receptacle

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Clockwise and counterclockwise

Air Flow Rate:

115.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.030 horsepower

Housing Inside Diameter:

4.517 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Tandem design, 4.688 in. Sq flange both ends of venturi tubes w/hole ea corner, 65 cfm min at 0.3 in. Water

Frequency In Hertz:

60.0

Material:

Zinc alloy housing

Surface Treatment:

Enamel housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0