

View Online at <https://aerobasegroup.com/nsn/4140-01-028-1595>

**Speed Adjustments:**

Single speed

**Length:**

3.000 inches

**Flow Direction:**

Outward and inward

**Environmental Protection:**

Humidity proof and shock proof and vibration proof and salt spray resistant

**Ambient Temperature At Full Rated Power:**

65.0 degrees celsius

**End Application:**

Nato seasparrow sms project

**Electrical Connection Type:**

Connector receptacle

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise and counterclockwise

**Air Flow Rate:**

115.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.030 horsepower

**Housing Inside Diameter:**

4.517 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Special Features:**

Tandem design, 4.688 in. Sq flange both ends of venturi tubes w/hole ea corner, 65 cfm min at 0.3 in. Water

**Frequency In Hertz:**

60.0

**Material:**

Zinc alloy housing

**Surface Treatment:**

Enamel housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0