

View Online at <https://aerobasegroup.com/nsn/4140-01-032-0717>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

1.870 inches

Length:

1.580 inches

Flow Direction:

Outward

Environmental Protection:

Dustproof and fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 100.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

11000.0

Electrical Connection Type:

Connector

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 ring

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

32.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

0.022 horsepower

Housing Inside Diameter:

1.890 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Circumferential surface and exterior face of mtg rings to be free of paint and be electrically conductive, class h insulation motor windings, connector to mate w/ms27473e8f-35s connector

Frequency In Hertz:

400.0

Material:

Aluminum alloy

Quantity:

1

Surface Treatment:

Enamel lusterless

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0