

View Online at <https://aerobasegroup.com/nsn/4140-01-032-5745>

Stage Quantity:

1

Speed Adjustments:

Single speed

Length:

1.500 inches

Flow Direction:

Outward

Ambient Temperature At Full Rated Power:

100.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

4800.0

End Application:

Esm room box assembly, kollmorgen corporation

Electrical Connection Type:

Terminal

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 bolt

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

12.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.013 horsepower

Housing Inside Diameter:

1.990 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

W/double faced auxiliary accessory compartment panel, rectangular, approx 5.25 in. Lg, 2.75 in. W, w/fan centered on panel, inlet end flush w/panel, panel depth approx 1.25 in. W/interior fitted w/screw terminal connection facility and capacitor, wired to fan terminals, mtg bolts at ends of panel utilized as spacer for panel faces

Frequency In Hertz:

50.0 and 400.0

Material:

Aluminum alloy

Surface Treatment:

Enamel lusterless

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0