

View Online at <https://aerobasegroup.com/nsn/4140-01-035-5295>

Speed Adjustments:

Two speed

Length:

2.830 inches

Flow Direction:

Inward

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

2340.0

Electrical Connection Type:

Connector

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 clip and 2 rim

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

200.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.032 horsepower

Housing Inside Diameter:

6.812 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

Mtg clips furnished, additional performance ratings, 400 hz, 105 cfm at 0.0 in. Water, 1240 rpm, 50 hz 165 cfm at 0.0 in. Water, 1930 rpm

Frequency In Hertz:

50.0 and 60.0 and 400.0

Material:

Aluminum alloy

Surface Treatment:

Enamel lusterless

Surface Treatment Specification:

Tt-e-489 federal specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A087a0