

View Online at <https://aerobasegroup.com/nsn/4140-01-035-5530>

Length:

1.562 inches

Flow Direction:

Reversible

Operating Speed At Rated Capacity In Rpm:

22500.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

1.5 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Mounting Facility Type And Quantity:

1 clamp ring

Rotation Direction For Which Designed:

Clockwise and counterclockwise

Air Flow Rate:

22.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Housing Inside Diameter:

1.750 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

400.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Anodize housing outside and enamel housing outside

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response blade

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-a-8625 spec.