

View Online at <https://aerobasegroup.com/nsn/4140-01-038-4877>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

4.260 inches

**Length:**

5.000 inches

**Ambient Temperature At Full Rated Power:**

Not rated

**Operating Speed At Rated Capacity In Rpm:**

8800.0

**Electrical Connection Type:**

Terminal block

**Outlet Inside Width:**

0.750 inches

**Outlet Inside Height:**

1.250 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 4 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

40.0 cubic feet per minute

**Outlet Location:**

Bottom or top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.147 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Angular down and angular up and horizontal and vertical down and vertical up

**Phase:**

Single

**Special Features:**

Positioning when mtg determines discharge blast direction, class f insulation motor windings

**Height:**

5.360 inches

**Material:**

Steel

**Surface Treatment:**

Zinc blade

**Surface Treatment Specification:**

Qq-z-325, type 2, class 2 federal specification single treatment response

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0