

View Online at <https://aerobasegroup.com/nsn/4140-01-038-4877>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

4.260 inches

Length:

5.000 inches

Ambient Temperature At Full Rated Power:

Not rated

Operating Speed At Rated Capacity In Rpm:

8800.0

Electrical Connection Type:

Terminal block

Outlet Inside Width:

0.750 inches

Outlet Inside Height:

1.250 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 4 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

40.0 cubic feet per minute

Outlet Location:

Bottom or top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.147 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Phase:

Single

Special Features:

Positioning when mtg determines discharge blast direction, class f insulation motor windings

Height:

5.360 inches

Material:

Steel

Surface Treatment:

Zinc blade

Surface Treatment Specification:

Qq-z-325, type 2, class 2 federal specification single treatment response

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0