

View Online at <https://aerobasegroup.com/nsn/4140-01-038-6625>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

7.900 inches

**Length:**

6.890 inches

**Environmental Protection:**

Humidity proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 70.0 degrees celsius

**End Application:**

Aircraft, boeing aircraft corp, e-3a aircraft

**Electrical Connection Type:**

Wire lead

**Outlet Inside Diameter:**

1.500 inches

**Static Pressure At Specificationified Air Flow Rate:**

18.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

12.0 cubic feet per minute

**Outlet Location:**

Bottom and top

**Voltage In Volts And Current Type:**

28.0 ac

**Prime Mover Power Rating:**

0.100 horsepower

**Discharge Direction:**

Angular down and angular up and horizontal and vertical down and vertical up

**Phase:**

Two

**Special Features:**

Positioning when mtg determines discharge blast direction, max cfm rated at 30, 000 ft, additional rating at sea level 6 cfm at 18 in. Water

**Height:**

6.600 inches

**Style Designator:**

Fixed, round outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0