

View Online at <https://aerobasegroup.com/nsn/4140-01-043-5086>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

7.250 inches

**Length:**

6.125 inches

**Environmental Protection:**

Shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

72.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2600.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 bracket and 4 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

400.0 cubic feet per minute

**Voltage In Volts And Current Type:**

208.0 ac or 220.0 ac

**Prime Mover Power Rating:**

0.552 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Three

**Special Features:**

Peripheral air discharge at right angle to axial air intake, w/capacitor, blower inlet plate not included

**Height:**

7.000 inches

**Material:**

Aluminum alloy

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0