

View Online at <https://aerobasegroup.com/nsn/4140-01-043-5087>

**Speed Adjustments:**

Single speed

**Length:**

0.984 inches

**Flow Direction:**

Inward

**Ambient Temperature At Full Rated Power:**

-40.0 degrees celsius and 70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3300.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

44.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.018 horsepower

**Housing Inside Diameter:**

3.543 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Special Features:**

3.622 in. Sq flange w/hole ea corner at both ends of venturi tube

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Zinc housing

**Surface Treatment:**

Enamel semigloss housing

**Style Designator:**

Fixed

**Supplementary Features:**

Interim supplier, etri corp, 800 s. Madison street, burr ridge, ill., 60521

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0