

View Online at <https://aerobasegroup.com/nsn/4140-01-043-5087>

Speed Adjustments:

Single speed

Length:

0.984 inches

Flow Direction:

Inward

Ambient Temperature At Full Rated Power:

-40.0 degrees celsius and 70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3300.0

Electrical Connection Type:

Terminal

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

44.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.018 horsepower

Housing Inside Diameter:

3.543 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

3.622 in. Sq flange w/hole ea corner at both ends of venturi tube

Frequency In Hertz:

50.0 and 60.0

Material:

Zinc housing

Surface Treatment:

Enamel semigloss housing

Style Designator:

Fixed

Supplementary Features:

Interim supplier, etri corp, 800 s. Madison street, burr ridge, ill., 60521

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0