

View Online at <https://aerobasegroup.com/nsn/4140-01-043-5089>

Speed Adjustments:

Single speed

Width:

3.625 inches

Diameter:

3.375 inches

Length:

1.500 inches

Flow Direction:

Outward

Environmental Protection:

Dustproof and fungus resistant and moisture resistant and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-20.0 degrees fahrenheit and 158.0 degrees fahrenheit

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

46.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac or 230.0 ac

Prime Mover Power Rating:

0.030 horsepower

Housing Inside Diameter:

3.250 inches

Prime Mover Drive Shaft Bearing Type:

Sleeve

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Height:

3.625 inches

Material:

Zinc alloy housing

Surface Treatment:

Enamel semigloss housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0