

View Online at <https://aerobasegroup.com/nsn/4140-01-047-1920>

**Speed Adjustments:**

Single speed

**Width:**

19.000 inches

**Length:**

7.593 inches

**Ambient Temperature At Full Rated Power:**

-20.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Operating Speed At Rated Capacity In Rpm:**

3200.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 4 slot

**Rotation Direction For Which Designed:**

Clockwise and counterclockwise

**Features Provided:**

Air filter and louver

**Air Flow Rate:**

290.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.234 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Angular up

**Phase:**

Single

**Special Features:**

Twin discharge outlets on rear of housing w/angular up discharge

**Frequency In Hertz:**

50.0 and 60.0

**Height:**

5.250 inches

**Material:**

Steel

**Quantity:**

1

**Surface Treatment:**

Enamel semigloss housing

**Style Designator:**

Fixed, dual, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0