NSN 4140-01-055-9814

Tubeaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-01-055-9814

| view Offilite at https://aerobasegroup.com/hsh/+1+0-01-055-50 |
|--|
| Speed Adjustments: |
| Single speed |
| Width: |
| 4.685 inches |
| Length: |
| 1.500 inches |
| Flow Direction: |
| Outward |
| Ambient Tempurature At Full Rated Power: |
| -10.0 degrees celsius and 65.0 degrees celsius |
| Operating Speed At Rated Capacity In Rpm: |
| 3100.0 |
| Electrical Connection Type: |
| Terminal |
| Static Pressure At Specificationified Air Flow Rate: |
| 0.0 inches of water |
| Drive Type: |
| Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Type And Quantity: |
| 2 flange and 8 unthreaded hole |
| Rotation Direction For Which Designed: |
| Clockwise |
| Air Flow Rate: |
| 120.0 cubic feet per minute |
| Voltage In Volts And Current Type: |
| 230.0 ac |
| Prime Mover Power Rating: |
| 0.024 horsepower |
| Housing Inside Diameter: |
| 4.125 inches |
| Prime Mover Drive Shaft Bearing Type: |
| Sleeve |
| Phase: |
| Single |
| Special Features: |
| 4.68 in. Sq flange w/hole ea corner at both ends of venturi tube |

Frequency In Hertz: 50.0 and 60.0

NSN 4140-01-055-9814

Tubeaxial Fan - Page 2 of 2



| Height: |
|--------------------|
| 4.685 inches |
| Material: |
| Zinc alloy |
| Surface Treatment: |
| Enamel |
| Style Designator: |
| Fixed |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A087a0