

View Online at <https://aerobasegroup.com/nsn/4140-01-058-1393>

**Speed Adjustments:**

Single speed

**Diameter:**

1.870 inches

**Length:**

1.500 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Dustproof and fungus resistant and moisture resistant and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 100.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

19200.0

**Electrical Connection Type:**

Connector

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 rim

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

57.0 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

0.052 horsepower

**Housing Inside Diameter:**

1.900 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Special Features:**

Connector mates w/ms27473e8f-35s connector, mtg face of mtg rims and ends of venturi barrel free of paint and electrically conductive

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy

**Quantity:**

1

**Surface Treatment:**

Enamel

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0