

View Online at <https://aerobasegroup.com/nsn/4140-01-058-1968>

**Speed Adjustments:**

Single speed

**Width:**

Between 4.680 inches and 4.683 inches

**Length:**

1.500 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

5200.0

**Electrical Connection Type:**

Connector

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

180.000 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

37.0 watts

**Housing Inside Diameter:**

4.500 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Height:**

Between 4.680 inches and 4.683 inches

**Material:**

Aluminum

**Surface Treatment:**

Enamel gloss

**Surface Treatment Specification:**

Tt-e-489, type b federal specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0