

View Online at <https://aerobasegroup.com/nsn/4140-01-058-1968>

Speed Adjustments:

Single speed

Width:

Between 4.680 inches and 4.683 inches

Length:

1.500 inches

Flow Direction:

Inward

Environmental Protection:

Salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

5200.0

Electrical Connection Type:

Connector

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

180.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

37.0 watts

Housing Inside Diameter:

4.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Height:

Between 4.680 inches and 4.683 inches

Material:

Aluminum

Surface Treatment:

Enamel gloss

Surface Treatment Specification:

Tt-e-489, type b federal specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0