

View Online at <https://aerobasegroup.com/nsn/4140-01-062-4523>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

Between 10.437 inches and 10.687 inches

**Diameter:**

5.400 inches

**Length:**

Between 8.313 inches and 8.437 inches

**Environmental Protection:**

Moisture resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

0.0 degrees celsius and 55.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3000.0

**End Application:**

W/s: spruance class dd (963); ticonderoga class cg (47); kidd class ddg

**Electrical Connection Type:**

Terminal block

**Outlet Inside Width:**

Between 3.656 inches and 3.844 inches

**Outlet Inside Height:**

Between 3.156 inches and 3.344 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.75 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 bracket and 1 flange

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

400.000 cubic feet per minute

**Outlet Location:**

Bottom

**Voltage In Volts And Current Type:**

440.0 ac

**Prime Mover Power Rating:**

0.333 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Height:**

Between 8.563 inches and 8.687 inches

**Material:**

Steel

**Quantity:**

1

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A087a0