

View Online at <https://aerobasegroup.com/nsn/4140-01-066-7883>

Speed Adjustments:

Single speed

Length:

2.000 inches

Flow Direction:

Inward

Operating Speed At Rated Capacity In Rpm:

2850.0 and 3350.0

End Application:

An/sqq-34 carrier based asw module; deep submergence systems programs (dssp); over the horizon back scanner (oth-b) program (an/fps-118); teletype, model 28; missile, air-to-air, phoenix (aim-54); support equipment, b-52 aircraft; ticonderoga class cg (47); support equipment, mx peacekeeper missile; virginia class cgn (41); power conditioning continuation interface equip (pccie)

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim and 4 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

240.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

31.0 watts

Housing Inside Diameter:

6.500 inches

Phase:

Single

Special Features:

Feathered edge blades

Frequency In Hertz:

50.0 and 60.0

Material:

Plastic blade

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A087a0