

View Online at <https://aerobasegroup.com/nsn/4140-01-067-9904>

Speed Adjustments:

Single speed

Length:

6.000 inches

Flow Direction:

Inward

Ambient Temperature At Full Rated Power:

-65.0 degrees fahrenheit and 190.0 degrees fahrenheit

Operating Speed At Rated Capacity In Rpm:

3800.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

160.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

650.0 watts

Housing Inside Diameter:

6.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Designed for high density gas (sf6) application, ratings for high density gas per test document

Frequency In Hertz:

400.0

Material:

Aluminum alloy

Surface Treatment:

Anodize

Style Designator:

Fixed

Test Data Document:

97942-582r043 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0