

View Online at <https://aerobasegroup.com/nsn/4140-01-074-2219>

**Speed Adjustments:**

Single speed

**Width:**

3.625 inches

**Length:**

1.500 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Corrosion resistant and moisture resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-28.0 degrees celsius and 65.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2900.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

40.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Housing Inside Diameter:**

3.438 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

47.0 and 440.0

**Height:**

3.625 inches

**Material:**

Plastic polycarbonate blade

**Material Specification:**

Mil-b-23071 military specification 2nd material response housing

**Surface Treatment:**

Plastic blade

**Surface Treatment Specification:**

Mil-b-23071 military specification 2nd treatment response housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0

**Mil-std (military Standard):**

Mil-b-23071 spec.