

View Online at <https://aerobasegroup.com/nsn/4140-01-074-2219>

Speed Adjustments:

Single speed

Width:

3.625 inches

Length:

1.500 inches

Flow Direction:

Outward

Environmental Protection:

Corrosion resistant and moisture resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-28.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

2900.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

4 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

40.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Housing Inside Diameter:

3.438 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

47.0 and 440.0

Height:

3.625 inches

Material:

Plastic polycarbonate blade

Material Specification:

Mil-b-23071 military specification 2nd material response housing

Surface Treatment:

Plastic blade

Surface Treatment Specification:

Mil-b-23071 military specification 2nd treatment response housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-b-23071 spec.