

View Online at <https://aerobasegroup.com/nsn/4140-01-084-9300>

Stage Quantity:

1

Speed Adjustments:

Single speed

Width:

Between 5.300 inches and 5.420 inches

Diameter:

3.500 inches

Length:

Between 4.810 inches and 4.930 inches

Environmental Protection:

Humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

7600.0

Electrical Connection Type:

Wire lead

Outlet Inside Width:

Between 0.690 inches and 0.810 inches

Outlet Inside Height:

Between 1.190 inches and 1.310 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 4 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

31.000 cubic feet per minute

Outlet Location:

Bottom or top

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

0.045 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Phase:

Three

Height:

Between 4.940 inches and 5.060 inches

Material:

Steel housing

Quantity:

1

Surface Treatment:

Chromate zinc housing

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0