

View Online at <https://aerobasegroup.com/nsn/4140-01-084-9300>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

Between 5.300 inches and 5.420 inches

**Diameter:**

3.500 inches

**Length:**

Between 4.810 inches and 4.930 inches

**Environmental Protection:**

Humidity proof and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 65.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

7600.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

Between 0.690 inches and 0.810 inches

**Outlet Inside Height:**

Between 1.190 inches and 1.310 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 4 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

31.000 cubic feet per minute

**Outlet Location:**

Bottom or top

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

0.045 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Angular down and angular up and horizontal and vertical down and vertical up

**Phase:**

Three

**Height:**

Between 4.940 inches and 5.060 inches

**Material:**

Steel housing

**Quantity:**

1

**Surface Treatment:**

Chromate zinc housing

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0