

View Online at <https://aerobasegroup.com/nsn/4140-01-088-7511>

Speed Adjustments:

Single speed

Length:

2.000 inches

Flow Direction:

Inward

Environmental Protection:

Dustproof and explosion proof and fungus proof and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

22500.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Radio interference shielding

Air Flow Rate:

225.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

95.0 watts

Housing Inside Diameter:

3.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Keyed bearings and special lubricant

Frequency In Hertz:

400.0

Material:

Aluminum alloy

Surface Treatment:

Enamel

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0