Centrifugal Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-01-089-8003

Stage Quantity:
1
Speed Adjustments:
Single speed
Width:
10.900 inches
Diameter:
6.000 inches
Length:
8.620 inches
Environmental Protection:
Moisture resistant and shock proof
Ambient Tempurature At Full Rated Power:
-55.0 degrees celsius and 71.0 degrees celsius
Operating Speed At Rated Capacity In Rpm:
3500.0
Electrical Connection Type: Terminal box
Outlet Inside Width:
3.090 inches
Outlet Inside Height:
2.280 inches
Static Pressure At Specificationified Air Flow Rate:
0.0 inches of water
Drive Type:
Prime Mover Type:
Electric motor
Inclosure Type:
Inclosure Type: Fully enclosed
Inclosure Type: Fully enclosed Mounting Facility Type And Quantity:
Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 1 clamp ring and 8 threaded insert
Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 1 clamp ring and 8 threaded insert Rotation Direction For Which Designed:
Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 1 clamp ring and 8 threaded insert Rotation Direction For Which Designed: Counterclockwise
Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 1 clamp ring and 8 threaded insert Rotation Direction For Which Designed:
Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 1 clamp ring and 8 threaded insert Rotation Direction For Which Designed: Counterclockwise
Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 1 clamp ring and 8 threaded insert Rotation Direction For Which Designed: Counterclockwise Features Provided:
Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 1 clamp ring and 8 threaded insert Rotation Direction For Which Designed: Counterclockwise Features Provided: Safety impeller guard
Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 1 clamp ring and 8 threaded insert Rotation Direction For Which Designed: Counterclockwise Features Provided: Safety impeller guard Air Flow Rate:
Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 1 clamp ring and 8 threaded insert Rotation Direction For Which Designed: Counterclockwise Features Provided: Safety impeller guard Air Flow Rate: 340.0 cubic feet per minute
Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 1 clamp ring and 8 threaded insert Rotation Direction For Which Designed: Counterclockwise Features Provided: Safety impeller guard Air Flow Rate: 340.0 cubic feet per minute Outlet Location:

NSN 4140-01-089-8003

Centrifugal Fan - Page 2 of 2



Prime Mover Power Rating: 0.965 horsepower Prime Mover Drive Shaft Bearing Type: Ball **Discharge Direction:** Vertical up Phase: Three Height: 9.640 inches Material: Steel Quantity: 1 Surface Treatment: Zinc blade Style Designator: Fixed, rectangular outlets Shelf Life: N/a Unit Of Measure: ---Demilitarization:

No Fiig:

A087a0