

View Online at <https://aerobasegroup.com/nsn/4140-01-101-8643>

Speed Adjustments:

Single speed

Width:

3.125 inches

Length:

1.645 inches

Flow Direction:

Outward

Ambient Temperature At Full Rated Power:

-28.0 degrees celsius and 70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

1950.0

Electrical Connection Type:

Terminal

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

21.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.007 horsepower

Housing Inside Diameter:

3.000 inches

Prime Mover Drive Shaft Bearing Type:

Sleeve

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Height:

3.125 inches

Material:

Zinc alloy housing

Unpackaged Unit Weight:

1.125 pounds

Surface Treatment:

Enamel lusterless housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0