

View Online at <https://aerobasegroup.com/nsn/4140-01-101-8643>

**Speed Adjustments:**

Single speed

**Width:**

3.125 inches

**Length:**

1.645 inches

**Flow Direction:**

Outward

**Ambient Temperature At Full Rated Power:**

-28.0 degrees celsius and 70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

1950.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

21.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.007 horsepower

**Housing Inside Diameter:**

3.000 inches

**Prime Mover Drive Shaft Bearing Type:**

Sleeve

**Phase:**

Single

**Frequency In Hertz:**

50.0 and 60.0

**Height:**

3.125 inches

**Material:**

Zinc alloy housing

**Unpackaged Unit Weight:**

1.125 pounds

**Surface Treatment:**

Enamel lusterless housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0