

View Online at <https://aerobasegroup.com/nsn/4140-01-110-1980>

**Speed Adjustments:**

Single speed

**Width:**

Between 3.118 inches and 3.142 inches

**Length:**

Between 3.118 inches and 3.142 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Moisture resistant

**Ambient Temperature At Full Rated Power:**

-20.0 degrees celsius and 80.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3200.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

38.0 cubic feet per minute

**Voltage In Volts And Current Type:**

12.0 dc

**Prime Mover Power Rating:**

0.003 horsepower

**Housing Inside Diameter:**

Between 2.805 inches and 2.825 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Err Default:**

Err default

**Height:**

Between 1.492 inches and 1.508 inches

**Material:**

Aluminum alloy housing

**Unpackaged Unit Weight:**

1.135 pounds

**Surface Treatment:**

Varnish

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0