

View Online at <https://aerobasegroup.com/nsn/4140-01-114-5351>

**Speed Adjustments:**

Single speed

**Width:**

7.940 inches

**Length:**

5.000 inches

**Environmental Protection:**

Humidity proof and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

50.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3250.0

**Electrical Connection Type:**

Terminal block

**Outlet Inside Width:**

2.020 inches

**Outlet Inside Height:**

2.120 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 clamp and 4 threaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

142.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Vertical up

**Phase:**

Single

**Height:**

4.750 inches

**Material:**

Steel

**Surface Treatment:**

Zinc blade

**Style Designator:**

Fixed, dual impeller, rectangular outlet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0